

## Bretter, Rahmen, Dielen

### Heimische Fichte

4-seitig gehobelt

Kanten gerundet

13 % Holzfeuchte



| Stärke/<br>Breite<br>in mm | Art      | Gelb hinterlegte Längen sind<br>Produktionslängen in Meter |  |  |  |     |     |     |     |     |     | Stück<br>pro<br>Bund | Stück<br>pro<br>Hub | 4-seitig<br>I/II<br>EUR/lfm. | Qualität<br>I/III<br>EUR/lfm. | Konstrukt.<br>Holz<br>EUR/lfm. |             |    |             |
|----------------------------|----------|--|--|--|--|-----|-----|-----|-----|-----|-----|----------------------|---------------------|------------------------------|-------------------------------|--------------------------------|-------------|----|-------------|
|                            |          |  |  |  |  |     |     |     |     |     |     |                      |                     |                              |                               |                                |             |    |             |
| 30 / 30                    | --       |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 |     | 5,0                  |                     |                              | 12                            | 540                            | <b>0,00</b> | -- | ---         |
| 30 / 50                    | --       |  |  |  |  | 2,0 | 2,5 | 3,0 | 3,5 | 4,0 | 4,5 | 5,0                  |                     |                              | 6                             | 300                            | <b>0,00</b> | -- | <b>0,00</b> |
| 30 / 60                    | --       |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 | 4,5 | 5,0                  |                     |                              | 6                             | 270                            | <b>0,00</b> | -- | <b>0,00</b> |
| 30 / 80                    | --       |  |  |  |  | 2,0 | 2,5 | 3,0 | 3,5 | 4,0 | 4,5 | 5,0                  |                     |                              | --                            | 208                            | <b>0,00</b> | -- | <b>0,00</b> |
| 30 / 120                   | --       |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 |     | 5,0                  |                     |                              | --                            | 144                            | <b>0,00</b> | -- | ---         |
| 30 / 160                   | --       |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 |     | 5,0                  | 6,0                 |                              | --                            | 96                             | <b>0,00</b> | -- | ---         |
| 30 / 200                   | --       |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 |     | 5,0                  |                     |                              | --                            | 80                             | <b>0,00</b> | -- | ---         |
| 30 / 250                   | --       |  |  |  |  | 2,0 | 2,5 | 3,0 | 3,5 | 4,0 |     | 5,0                  |                     |                              | --                            | --                             | <b>0,00</b> | -- | ---         |
| 30 / 300                   | --       |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 |     | 5,0                  |                     |                              | --                            | --                             | <b>0,00</b> | -- | ---         |
| 35 / 35                    | kernfrei |  |  |  |  | 2,0 | 2,5 | 3,0 | 3,5 | 4,0 | 4,5 | 5,0                  |                     |                              | 9                             | 450                            | <b>0,00</b> | -- | ---         |
| 35 / 55                    | kernfrei |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 | 4,5 | 5,0                  |                     |                              | 6                             | 270                            | <b>0,00</b> | -- | <b>0,00</b> |
| 35 / 80                    | kernfrei |  |  |  |  | 2,0 | 2,5 | 3,0 | 3,5 | 4,0 |     | 5,0                  |                     |                              | --                            | 182                            | <b>0,00</b> | -- | ---         |
| 35 / 112                   | kernfrei |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 |     | 5,0                  |                     |                              | --                            | 126                            | <b>0,00</b> | -- | ---         |
| 40 / 40                    | kernfrei |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 |     | 5,0                  |                     |                              | 6                             | 312                            | <b>0,00</b> | -- | <b>0,00</b> |
| 40 / 60                    | kernfrei |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 |     | 5,0                  |                     |                              | 4                             | 216                            | <b>0,00</b> | -- | <b>0,00</b> |
| 40 / 80                    | kernfrei |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 |     | 5,0                  | 6,0                 |                              | --                            | 156                            | <b>0,00</b> | -- | <b>0,00</b> |
| 40 / 100                   | kernfrei |  |  |  |  | 2,0 | 2,5 | 3,0 | 3,5 | 4,0 |     | 5,0                  | 6,0                 |                              | --                            | 120                            | <b>0,00</b> | -- | ---         |
| 40 / 120                   | kernfrei |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 |     | 5,0                  | 6,0                 |                              | --                            | 108                            | <b>0,00</b> | -- | ---         |
| 40 / 160                   | kernfrei |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 |     | 5,0                  | 6,0                 |                              | --                            | 72                             | <b>0,00</b> | -- | ---         |
| 40 / 200                   | kernfrei |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 | 4,5 | 5,0                  | 6,0                 |                              | --                            | 60                             | <b>0,00</b> | -- | ---         |
| 40 / 250                   | --       |  |  |  |  | 2,0 | 2,5 | 3,0 |     | 4,0 |     | 5,0                  | 6,0                 |                              | --                            | 44                             | <b>0,00</b> | -- | ---         |

Anfallslängen, Qualität I/III und Konstruktionsholz nach Verfügbarkeit

10 % Rabatt auf blau hinterlegte Anfallslängen, sofern verfügbar

8 % Aufschlag bei 6,0 m Länge



Anwendungsbeispiel: Pflanzenrost