


## Rahmen, Dielen

### Heimische Fichte

4-seitig gehobelt

Kanten gerundet

13 % Holzfeuchte



Stärke/ Breite in mm	Art	Gelb hinterlegte Längen sind Produktionslängen in Meter										Stück pro Bund	Stück pro Hub	4-seitig I/II EUR/lfm.	Qualität I/III EUR/lfm.	Konstrukt. Holz EUR/lfm.			
		2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0									
45 / 45	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0			6	264		--	---
50 / 50	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0			4	200		--	
50 / 70	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0			4	150		--	
50 / 120	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	90		--	
50 / 160	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	60		--	---
50 / 200	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	50		--	---
50 / 250	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0			--	--		--	---
50 / 300	--					2,0	2,5	3,0	3,5	4,0	4,5	5,0			--	--		--	---
55 / 55	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0			4	180		--	---
55 / 75	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0			--	126		--	
60 / 60	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0			--	136		--	
60 / 80	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	104		--	
60 / 120	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	72		--	
60 / 160	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	48		--	---
60 / 300	--					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	--		--	---

Anfallslängen, Qualität I/III und Konstruktionsholz nach Verfügbarkeit

10 % Rabatt auf blau hinterlegte Anfallslängen

8 % Aufschlag bei 6,0 m Länge



Anwendungsbeispiel: Tomatenhaus



Anwendungsbeispiel: Außentreppe