

Rahmen, Dielen

Heimische Lärche

glatt gehobelt

Kanten gerundet

14 % Holzfeuchte



Stärke/ Breite in mm	Art	Gelb hinterlegte Längen sind Produktionslängen in Meter														Stück pro Bund	Stück pro Hub	Qualität I/II EUR/lfm.	Konstrukt. Holz EUR/lfm.
		1,0	1,25	1,50	1,75	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	6,0				
60 / 60	meist kernfrei	1,0	1,25	1,50	1,75	2,0	2,5	3,0	3,5	4,0	4,5	5,0			--	136			
60 / 80	meist kernfrei	1,0	1,25	1,50	1,75	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	104			
60 / 120	meist Halbrißts	1,0	1,25	1,50	1,75	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	72			
60 / 300	meist kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	24		--	
70 / 70	meist kernfrei	1,0	1,25	1,50	1,75	2,0	2,5	3,0	3,5	4,0	4,5	5,0			--	105			
80 / 80	meist kernfrei	1,0	1,25	1,50	1,75	2,0	2,5	3,0	3,5	4,0	4,5	5,0			--	78			
80 / 120	meist kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	54			
80 / 160	meist kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	36			
90 / 90	kernfrei	1,0	1,25	1,50	1,75	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	66			
100 / 100	kernfrei	1,0	1,25	1,50	1,75	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	50			
100 / 120	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	45			
100 / 160	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	30			
100 / 200	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	25			
120 / 120	kernfrei	1,0	1,25	1,50	1,75	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	36			
120 / 160	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	24			
120 / 200	kernfrei					2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	20			
140 / 140	kernfrei	1,0	1,25	1,50	1,75	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	--	28			

- Anfallslängen und Konstruktionsholz nach Verfügbarkeit
- 20 % Rabatt auf orange hinterlegte Anfallslängen
- 10 % Rabatt auf blau hinterlegte Anfallslängen
- 8 % Aufschlag bei 6,0 m Länge



Anwendungsbeispiel: Untersetzer für Topfpflanzen